

USB 3.1 Gen 1 PCIe Host Adapter Card

- Latest Fresco FL1100 chipset
- Low rise for 1 U chassis
- 4 x USB 3.1 Gen 1 ports (2 external ports plus 2 via internal head connector*)
- Support power delivery for 4 cameras



U3-PCIE2-2P01X SPECIFICATIONS

General Specifications	
Chipset	Fresco Logic FL-1100
Bus type	PCI Express 2 (x1 connector)
Bus width	x1 lane PCI Express operable in x1, x4, x8, x16 slots
Transfer Rate	5 Gbps
Power	Power by PCIe 10 W max, Power by IDE 20 W max
Hardware certifications	RoHS, CE, FCC
Operating temperature	0° C to 45° C
Storage temperature	-30° C to 60° C
Dimensions	6.75 x 6.8 x 12 cm (Length x Width x height of end bracket)
Accessories	Low-profile PCIe bracket included (8cm)

*Internal 20-pin connector can be expanded using a 20-pin adapter (not included). Vendor and part number for the 20-pin adapter: Kingwin KW-PCI2USB3, Orico PCI20P-OU32

FLIR Integrated Imaging Solutions

CANADA

12051 Riverside Way
Richmond, BC, Canada
V6W 1K7
T: +1 866.765.0827 (toll free)
T: +1 604.242.9937
F: +1 604.242.9938
E: mv-sales@flir.com
www.flir.com/iis

USA

T: +1 866.765.0827 (toll free)
E: mv-na-sales@flir.com

EUROPE

T: +49 7141 488817-0
F: +49 7141 488817-99
E: mv-eusales@flir.com

CHINA

T: +86 10 8215 9938
F: +86 10 8215 9936
E: mv-chinasales@flir.com
www.ptgreychina.com

ASIA

E: mv-asiasales@flir.com

DISTRIBUTORS

JAPAN

ViewPLUS Inc. (www.viewplus.co.jp)

KOREA

CYLOD Co., Ltd. (www.cylod.com)

CHINA

LUSTER LightVision (www.lusterinc.com)

SINGAPORE, THAILAND, MALAYSIA

Voltrium Systems (www.voltrium.com.sg)

TAIWAN

Apo Star Co., Ltd. (www.apostar.com.tw)

UNITED KINGDOM AND IRELAND

ClearView Imaging (www.clearviewimaging.co.uk)

©2017 FLIR® Integrated Imaging Solutions Inc. All rights reserved.

Names and marks appearing on the products herein are either registered trademarks or trademarks of FLIR® Systems, Inc. and/or its subsidiaries.