



## DUAL-BAND I<sup>2</sup> & THERMAL WEAPON SIGHT

# MilSight® S140-D ADUNS

Designed to mount on any MIL-STD-1913 rail interface forward of an existing scope, the FLIR MilSight® S140-D ADUNS (advanced dual-band universal night sight) offers ultimate mission flexibility. Use as a thermal weapon sight, on a spotting scope for long-range reconnaissance, or as a handheld observation device. The ADUNS system offers high-resolution blended thermal and image intensified night vision that provides crisp imagery through total darkness, fog, smoke, dust, and many other obscurants.

Snipers can choose to view targets in either thermal, I<sup>2</sup>, or blended channels to optimize target detection and recognition. I<sup>2</sup> penetrates glass and provides IFF while thermal circumvents camouflage and provides rapid target detection. Configurable with white and green phosphor tubes for high-performance US and exportable versions. White phosphor provides a natural looking scene while high-resolution 72 lp/mm in either green or white phosphor produces sharper scene details for longer-range target engagements.

### FEATURES

#### ADJUSTABLE BLENDING OF IR AND I<sup>2</sup>

High-resolution blended thermal/image-intensified light night weapon sight provides crisp imagery in complete darkness and under foggy, smoky, or dusty conditions.

#### BORESIGHT MAINTAINED AFTER WEAPON DISCHARGE

Coaxial design aligns point of aim and point of impact in thermal, I<sup>2</sup>, and blended views for increased target engagement capability and lethality.

#### COMPACT, LIGHT, AND RUGGED

Highly portable design reduces operator fatigue and large, rugged controls for basic image adjustments means no complex menus to navigate.

#### SHOCK MITIGATION MAINTAINS BORESIGHT

The proprietary FLIR Shock Mitigation System™ (SMS™) absorbs and dissipates high shock loads while extending tube life and maintaining zero.

#### MISSION FLEXIBILITY

Functions as a thermal weapon sight, a spotting scope for long-range reconna

### APPLICATIONS

TARGET ACQUISITION

RECONNAISSANCE

COVERT OPERATIONS

SURVEILLANCE

SPECIALITY LAW ENFORCEMENT

## SPECIFICATIONS

System Characteristics		SNIPER (S140-D)
Magnification	Unity	
Optimum Dayscope Magnification	4x to 12x	
Focus Range	15 m to Infinity	
Channel-to-Channel Parallax	None at any range	
I2 Field of View	8.8°	
IR Field of View	7.1° H x 5.3° V	
IR IFOV	0.19 mr	
IR Objective	88 mm, f/0.88	
VisNIR Objective	91 mm, f/0.97	
Image Intensifier Gain	75,000 max	
Output Aperture	40 mm	
Boresight Characteristics		
Accuracy	Factory Aligned to 1 MOA or Better	
Repeatability	Within 1 MOA	
Power		
Power requirements	4 each AA Li (L91)	
Dimensions, Weight & Mounting		
Shock Mitigation System™ (SMS™)	Standard Feature	
Interface (to MIL-STD 1913)	Dual Locking Levers	
Dimensions	11.2" (28.5 cm) x 4.6" (11.7 cm) x 4.3" (11 cm)	
Weight (w/o batteries)	4.5 lbs (2.25 kg)	
Center Height Above Rail	1.5" typical	
Interfaces		
Command and Control	On camera and remote pendant	
Video	External video - Thermal	



### AMERICAS

FLIR Systems, Inc.  
Corporate Headquarters  
27700 SW Parkway Ave  
Wilsonville, OR 97070  
Office: +1 877.773.3547

FLIR Systems, Inc.  
DC Headquarters  
1201 S. Joyce Street  
Suite C006  
Arlington, VA 22202  
Office: +1 703.682.3400

### EUROPE

FLIR Systems  
2 Kings Hill Avenue - Kings Hill  
West Malling, Kent ME19 4AQ  
United Kingdom  
Office: +44 (0)1732 220 011  
Fax: +44 (0)1732 843 707

FLIR Systems AB  
Antennvägen 6,  
PO Box 737  
SE-187 66 Täby  
Sweden  
Office: +46 (0)8 753 25 00

### MIDDLE EAST

FLIR Systems B.V. - Abu Dhabi  
Wadi Al Fey St.  
Building 60, Office # 302  
New Ministries Exit / Khalifa Park Area  
Abu Dhabi, U.A.E.  
Office: +971 2 666 1561  
e-Fax: +1 503 914 1591

FLIR Systems Saudi Arabia  
Office 127, First Floor  
Akaria Plaza Building, Olaya Street  
Riyadh, 11481, Saudi Arabia  
Office: +966 11 464 5323  
Fax: +966 11 464 0438

### ASIA

FLIR Systems Japan K.K.  
Meguro Tokyu Bldg. 5F,  
2-13-17  
Kami-Osaki, Shinagawa-ku.  
Tokyo, 141-0021, Japan  
Office: +81-3-6721-6648



For More Information contact  
[surveillance\\_sales@flir.com](mailto:surveillance_sales@flir.com)

[www.flir.com](http://www.flir.com)  
NASDAQ: FLIR

Equipment described herein is subject to US export regulations and may require a license prior to export. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2019 FLIR Systems, Inc. All rights reserved. 12/03/19

19-2546-SUR-MilsightS140-D-ADUNS LTR



The World's Sixth Sense®