



COMPACT MULTI-SENSOR GYRO-STABILIZED SURVEILLANCE SYSTEM

FLIR UltraFORCE® 275-HD

Extremely low SWaP makes the UltraFORCE 275-HD the optimal choice for weight, power and footprint-constrained platforms. The system delivers multi-spectral HD imaging performance for airborne homeland security, combat, patrol, surveillance, reconnaissance, and search and rescue programs. Durable, long endurance design makes the UltraFORCE 275-HD the ideal choice for lightweight manned and unmanned airborne platforms. Built in Europe with no U.S.-sourced components, the UltraFORCE 275-HD is ITAR-free, increasing exportability and freedom of movement within Europe.

The UltraFORCE 275-HD delivers high-quality, real-time full motion video (FMV) while having the lowest weight in its 10" to 12" turret class. It incorporates high performance TV and IR imaging payloads, both with continuous zoom optics, to provide long-range identification and covert operation at high standoff ranges. Single LRU architecture simplifies installation, and integrated IMU and GPS provide accurate geo-referencing for peripheral systems.

FEATURES

SIGNIFICANT SWaP ADVANTAGES

Single LRU and lowest weight in its 10" to 12" turret class make it easy to install on weight, power, and footprint-constrained platforms, without compromising endurance.

ITAR-FREE FLEXIBILITY

Built in Europe with no U.S.-sourced components, the UltraFORCE family offers increased exportability.

CONTINUOUS ZOOM

Continuous zoom, high performance optics on all imaging sensors provide uninterrupted video of evidential quality and reduces operator workload to maintain target visibility during zoom.

EASA FORM 1 COMPLIANT

This certificate of airworthiness simplifies installation and certification, and eliminates the need for qualification when installed on approved aircraft mounts.

RICH METADATA OUTPUT

UltraFORCE 275-HD delivers full HD video with embedded metadata fully compliant to STANAG and MISB standards.

APPLICATIONS

COUNTER DRUG AND PEOPLE SMUGGLING

HOMELAND SECURITY

PATROL

SURVEILLANCE

RECONNAISSANCE

SEARCH & RESCUE

BORDER PROTECTION

SPECIFICATIONS

Thermal Imaging Performance

Sensor Type	3rd gen 640 x 512 3-5 μ m MCT focal plane array
Image Enhancements	Non Uniformity Correction, Bad Pixel Replacement, AGC (Automatic Gain Control), Histogram, Equalization, Digital Details Enhancement (Tunable)
FOV	Continuous zoom 28° to 1.83°
Ezoom	2x

Daylight Imaging Performance

Sensor	High Definition CMOS
Resolution	1080x720 or 1920x1080
FOV	Continuous zoom 45° to 2.3°
Minimum Illumination	0.01 lux color; 0.006 lux monochrome

Gimbal Specifications

LOS Pan range	360 degrees continuous
LOS Tilt range	+20 / -120 degrees
AZ/EL slew rate	Up to 60°/s
Stow	Magnetically held in stow position

Electronics Control Unit

Hand Controller Unit	0.8 kg, 230 mm Height
----------------------	-----------------------

Interfaces

ARINC 429, RS232/422 and other interfaces to support navigation systems, moving maps, radars, searchlights, and GPS

Outputs

Video	HD-SDI 720p / 1080p
-------	---------------------

Power


Power requirements	22-30 VDC < 150 W, 75 W typical
--------------------	---------------------------------

Overview

Gimbal size	275 mm (D) x 378.5 mm (H) / Approx. 11 in (D) x 15 in (H)
Gimbal weight	16 kg / 35 lbs
Environmental	RTCA DO-160E

Options

Auto-Tracker
Laser Range Finder
Laser Pointer (Covert)
Eyesafe Visible Laser Pointer
Laser Illuminator
IMU & GPS
Control Unit



AMERICAS

FLIR Systems, Inc.
Corporate Headquarters
27700 SW Parkway Ave
Wilsonville, OR 97070
Office: +1 877.773.3547

FLIR Systems, Inc.
DC Headquarters
1201 S. Joyce Street
Suite C006
Arlington, VA 22202
Office: +1 703.682.3400

EUROPE

FLIR Systems
2 Kings Hill Avenue - Kings Hill
West Malling, Kent ME19 4AQ
United Kingdom
Office: +44 (0)1732 220 011
Fax: +44 (0)1732 843 707

FLIR Systems AB
Antennvägen 6,
PO Box 737
SE-187 66 Täby
Sweden
Office: +46 (0)8 753 25 00

MIDDLE EAST

FLIR Systems B.V. - Abu Dhabi
Wadi Al Fey St.
Building 60, Office # 302
New Ministries Exit / Khalifa Park Area
Abu Dhabi, U.A.E.
Office: +971 2 666 1561
e-Fax: +1 503 914 1591

FLIR Systems Saudi Arabia
Office 127, First Floor
Akaria Plaza Building, Olaya Street
Riyadh, 11481, Saudi Arabia
Office: +966 11 464 5323
Fax: +966 11 464 0438

ASIA

FLIR Systems Japan K.K.
Meguro Tokyu Bldg. 5F,
2-13-17
Kami-Osaki, Shinagawa-ku.
Tokyo, 141-0021, Japan
Office: +81-3-6721-6648

For More Information contact
surveillance_sales@flir.com

www.flir.com
NASDAQ: FLIR

Equipment described herein pertains to a European Union origin product that is controlled as dual-use item by the European Union government. It may be subject to US Jurisdictions when in the United States or possessed by a US person and may require authorization to re-transfer to or share with a foreign person (not a US Person). Imagery for illustration purposes only. Specifications are subject to change without notice. ©2020 FLIR Systems, Inc. All rights reserved. Revised 09/08/20

20-1193-SUR UltraForce 275-HD-SS LTR



The World's Sixth Sense®