



## AIRBORNE VEHICLE RECONNAISSANCE SYSTEM (VRS) FOR MILITARY OPERATIONS

# Black Hornet VRS

The FLIR Black Hornet Vehicle Reconnaissance System (VRS) equips armored or mechanized vehicles with an immediate, organic, and self-contained surveillance and reconnaissance system. Adapted from the Black Hornet Personal Reconnaissance System (PRS), the VRS extends the game-changing and lifesaving capability of the Black Hornet nano-UAV. The launch unit mounts externally and fully integrates within the vehicle to create a real time situational awareness RSTA airborne system for crews protected inside.

The world's smallest and lightest UAV reconnaissance system designed for autonomous operations from vehicles, Black Hornet VRS is optimal when vehicles need mission-critical SA or BLOS targeting capabilities. The launch unit includes four UAVs for automatic launching capability, continuous coverage, and simultaneous missions. The complete system is easily integrated with modern battlefield management systems (BMS) and is vehicle platform independent. With limited training, personnel can operate the system quickly and within existing systems training programs.

### FEATURES

#### IMMEDIATE COVERT SITUATIONAL AWARENESS

Save lives and minimize collateral damage. Detect and identify threats day and night without being detected. Increase speed of movement and expand maneuver options.

#### NON-SPECIALIST NANO UAV SYSTEM

Seamlessly integrated into the vehicle control systems, crew members need only minimal training for successful deployment.

#### EXTREMELY COVERT AIRBORNE SENSOR

Extremely low visual and audible signatures allow covert operation and increased security.

#### BEYOND VISUAL LINE-OF-SIGHT CAPABILITY (BLOS)

Expand visual range in complex and urban environments. Rapidly engage targets beyond visual line-of-sight, and conduct real-time weapon effectiveness assessment.

#### RESILIENT AND BATTLE-TESTED

Combat-proven on the battlefield by NATO forces.

### APPLICATIONS

IMMEDIATE ISR

COVERT OPERATIONS

SITUATIONAL AWARENESS

BEYOND LINE-OF-SIGHT RECONNAISSANCE

FORCE PROTECTION

Due to its extremely small size and light weight, the UAV is regarded by several Military Aviation Authorities to expose minimal risk to other aircraft or personnel on the ground, and as such simplifies the required certification process and minimizes the need for airspace clearance to operate. This allows the user to launch a UAV immediately and operate with maximum freedom of operation. Different national rules and regulations may apply. FLIR UAS has gained approval from the US Federal Aviation Authorities to operate the Black Hornet without restrictions in CONUS (limitations apply in areas close to airports).

## SPECIFICATIONS

### Black Hornet 3 Specifications

Rotor diameter	123 mm (4.8 in)
Total length	168 mm (6.6 in)
Weight	< 33 grams (1.16 oz)
<b>Signature</b>	
Visual detection	Unaided <20 m (65.6 ft)
Audio	< 25 dBA @ 50 m (164 ft)
<b>Payload</b>	
Replaceable	Yes
Day Imager	2 EO Cameras
Night Imager	Fused thermal and EO
<b>Performance</b>	
Endurance	Up to 25 minutes
Max. speed	6 m/sec ground speed (~20 ft/sec)
<b>Environment</b>	
Temperature	-10°C to +43°C
Wind	>15 knots/gust 20 knots
Precipitation	2.5 mm (.1 in)/hr (Light rain)
<b>Data Link</b>	
Frequency	Details on request
Radio Range	2 km (1.24 mi)
Performance	Encrypted, dynamic power, frequency hopping, beyond line-of-sight
<b>Resolution</b>	
EO Video	640 x 480
EO Snapshot	1600 x 1200
Thermal Imaging Video	160 x 120
Thermal Imaging Snapshot	160 x 120
<b>Flight modes</b>	
Auto and Manual Hover & Stare Route and user selectable waypoint actions Automatic return Lost link	
<b>Navigation</b>	
GPS and GPS denied (Launch and Landing). Indoor capability	
<b>Mission Data</b>	
AES 256 encrypted Video, Snapshots, and Metadata STANAG 4609 and Cursor on Target (COT) compliant ATAK Compatible Can be integrated with selected BMS	

### VRS Launch Unit Specifications

Material	Aluminum
UAV Quantity	Four removable cassettes with heating and charging
Mounting	Mounted with shock absorbers between LU and mounting bracket
Deployment	Motorized lid for opening and closing for release of the UAV
Communications	Single or Dual radio for operations of one to two UAVs
Frequency	Details on request
Radio Range	2 km (1.24 mi)
Performance	Encrypted, dynamic power, frequency hopping, beyond line-of-sight
Control	Dual control or single
External Interfaces	Ethernet, USB, RS-232, HDMI
Sensors and Antennas	Wind sensor, UHF and GPS antenna
Vehicle Interface	Generic Vehicle Architecture (GVA Interface)
Standardization	STANAG 4609 and 4545
Power	10-32 V
Size	Width: 470 mm, Depth: 420 mm, Height: 260 mm
Weight	Weight: 23 kg
Ballistics Protection	Option
Qualifications	MIL-STD 461, 810 and 1275



#### AMERICAS

FLIR Systems, Inc.  
Corporate Headquarters  
27700 SW Parkway Ave  
Wilsonville, OR 97070  
Office: +1 877.773.3547

FLIR Systems, Inc.  
DC Headquarters  
1201 S. Joyce Street  
Suite C006  
Arlington, VA 22202  
Office: +1 703.682.3400

#### EUROPE

FLIR Systems  
2 Kings Hill Avenue - Kings Hill  
West Malling, Kent ME19 4AQ  
United Kingdom  
Office: +44 (0)1732 220 011  
Fax: +44 (0)1732 843 707

FLIR Systems AB  
Antennvägen 6,  
PO Box 737  
SE-187 66 Täby  
Sweden  
Office: +46 (0)8 753 25 00

#### MIDDLE EAST

FLIR Systems B.V. - Abu Dhabi  
Wadi Al Fey St.  
Building 60, Office # 302  
New Ministries Exit / Khalifa Park Area  
Abu Dhabi, U.A.E.  
Office: +971 2 666 1561  
e-Fax: +1 503 914 1591

FLIR Systems Saudi Arabia  
Office 127, First Floor  
Akaria Plaza Building, Olaya Street  
Riyadh, 11481, Saudi Arabia  
Office: +966 11 464 5323  
Fax: +966 11 464 0438

#### ASIA

FLIR Systems Japan K.K.  
Meguro Tokyu Bldg. 5F,  
2-13-17  
Kami-Osaki, Shinagawa-ku.  
Tokyo, 141-0021, Japan  
Office: +81-3-6721-6648



For More Information contact  
surveillance\_sales@flir.com

www.flir.com  
NASDAQ: FLIR

Equipment described herein is subject to US export regulations and may require a license prior to export. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2019 FLIR Systems, Inc. All rights reserved. 01/03/19

18-2137-SUR-Blackhornet-VRS-Specsheet LTR



The World's Sixth Sense®