



## MOBILE SURVEILLANCE AND DETERRENCE TOWER

# FLIR SkyWatch™

Rising over two stories, FLIR SkyWatch is a rugged, highly reinforced mobile surveillance platform that can withstand 60 mph winds while keeping the operator safe, comfortable, and focused. Portable and rapidly deployable, it provides a strategic perspective and symbolic deterrent. Customize payload with pan-tilt IR, night vision, visible-light cameras, in-cab controls, ground radar, monitors, Network Video Recorder (NVR), and searchlights. Designed for crowd control, high-crime area monitoring, and missing person command, SkyWatch easily moves to where the threat is.

SkyWatch safely raises and lowers in 90 seconds. Operators have 360° visibility from an ergonomic command desk in the temperature controlled cabin. Optional public address system, full-function siren, and roof-mounted, high-powered searchlights with internal pan/tilt control allow operators to alert ground support and crowds of an immediate threat. Wireless video streaming and remote control allow operators to take advantage of the elevated perspective without actually sitting in the cabin.

### FEATURES

#### RAPID DEPLOYMENT AND FULL PORTABILITY

Towable practically anywhere, one soldier or trained civilian can deploy SkyWatch in minutes, safely raising it in about 90 seconds.

#### POWERFUL MULTI-SENSOR CAPABILITY

All PTZ thermal/day or day/night cameras available and fully integrated into cab along with a 24" monitor, in cab controls and NVR. Wireless connectivity is also offered.

#### FLEXIBLE DISPLAY VIEWS

Full screen, split-screen display, and two fields-of-view within SkyWatch cab monitor as well as remote streaming video and camera control.

#### TEMPERATURE-CONTROLLED TOWER

Keep operator comfortable, protected against up to 60 mph gusts, and engaged in active surveillance.

#### SEE, FIND, DOCUMENT EFFICIENTLY

Payload options include fixed or pan-tilt IR, night vision, visible-light cameras, ground radar, NVR, and searchlights.

### APPLICATIONS

MAJOR VENUE CONTROL

HIGH-CRIME AREA MONITORING

MISSING PERSON COMMAND

LIMITED FORCE SUPPLEMENTATION

PERIMETER PROTECTION

GATE OVERWATCH

HIGH VALUE EQUIPMENT PROTECTION

PARKING LOT SURVEILLANCE AND DETECTION

## SKYWATCH™ DETAILS

Product Specifications	One Man Cab	Two Man Cab
Height – Transport (Tow)*	10' 10"	
Height – Transport (Truck)	9' 5"	
Width – Transport	8' 2"	
Length – Transport	23' 6"	24' 7"
Height – Cab Deployed	30' 6"	
Height – Operator Eye Level	27' 0"	
Width – Outriggers Deployed	19' 0"	
Approx. Gross System Weight (lbs)	11,550	12,600
Approx. Tongue Weight (lbs)	1,900	1,800
Trailer Components and Contents		
2 5/16 Ball	Standard	
Lunette Eye	Optional	
16K Single Axle 17.5" Dual Wheel	Standard	
Dual Pump Hydraulic Lifting System	Standard	
Hydraulic Reservoir (Gallons)	9	
Generator Specifications		
Gasoline Generator with 20 Gallon EVAP Fuel Tank	Optional	
Diesel 120 V Generator with 78 Gallon Fuel Tank	Standard	
Approx. Gas Generator Run Time	24 Hours	
Approx. Diesel Generator Run Time	5 Days	
Solar Battery Charging System for Generator Start	Standard	
Shore Power	Shore Power	
Officers Compartment & Contents		
Cab Width – Interior	4' 7"	
Cab Length – Interior	4' 7"	6' 7"
Cab Height – Interior	6' 5"	6' 5"
Cab Max Additional Weight (lbs) **	3,500	3,100
Window Type	Tinted Sliding	
Descent Camera and Alarm	Standard	
Blue Strobe Light	Standard	
Digital Winder Speed Meter	Standard	
Led Flood Lights (4)	Standard	
15K BTU Air Conditioner	Standard	
Harsh Climate Air Conditioner	Optional	
Swivel Chair	1	2

\* Values subject to change depending on selected optional configurations  
 \*\* Includes occupants, gear and selected optional configurations

Standard Features
AC and heating for operator comfort
LED floodlights on every side
Under cab safety camera
Strobe light and descent alarm
Tinted windows
Command desk
Digital windspeed meter
Generator and fuel tank
12 months parts & labor warranty
Additional Options
EO/IR (thermal) fixed/PTZ cameras with in-cab joystick control, monitor and NVR
Fixed or PTZ FLIR visible-light/IA night vision cameras with in-cab joystick control, monitor and NVR
Wireless video streaming and remote control
Ground surveillance radar
Public address system with 100-watt speakers and full-function siren
Roof-mounted, high-powered searchlights with internal pan/tilt control
Service maintenance plans



### AMERICAS

FLIR Systems, Inc.  
 Corporate Headquarters  
 27700 SW Parkway Ave  
 Wilsonville, OR 97070  
 Office: +1 877.773.3547

FLIR Systems, Inc.  
 DC Headquarters  
 1201 S. Joyce Street  
 Suite C006  
 Arlington, VA 22202  
 Office: +1 703.682.3400

### EUROPE

FLIR Systems  
 2 Kings Hill Avenue - Kings Hill  
 West Malling, Kent ME19 4AQ  
 United Kingdom  
 Office: +44 (0)1732 220 011  
 Fax: +44 (0)1732 843 707

FLIR Systems AB  
 Antennvägen 6,  
 PO Box 737  
 SE-187 66 Täby  
 Sweden  
 Office: +46 (0)8 753 25 00

### MIDDLE EAST

FLIR Systems B.V. - Abu Dhabi  
 Wadi Al Fey St.  
 Building 60, Office # 302  
 New Ministries Exit / Khalifa Park Area  
 Abu Dhabi, U.A.E.  
 Office: +971 2 666 1561  
 e-Fax: +1 503 914 1591

FLIR Systems Saudi Arabia  
 Office 127, First Floor  
 Akaria Plaza Building, Olaya Street  
 Riyadh, 11481, Saudi Arabia  
 Office: +966 11 464 5323  
 Fax: +966 11 464 0438

### ASIA

FLIR Systems Japan K.K.  
 Meguro Tokyo Bldg. 5F,  
 2-13-17  
 Kami-Osaki, Shinagawa-ku.  
 Tokyo, 141-0021, Japan  
 Office: +81-3-6721-6648

For More Information contact  
[surveillance\\_sales@flir.com](mailto:surveillance_sales@flir.com)

[www.flir.com](http://www.flir.com)  
 NASDAQ: FLIR

Equipment described herein is subject to US export regulations and may require a license prior to export. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2019 FLIR Systems, Inc. All rights reserved. 03/13/19

19-0499-SUR-Skywatch Specsheet A4



The World's Sixth Sense®