



MULTI-MISSION EO/IR SURVEILLANCE SENSOR

FLIR Star SAFIRE™ III

With thousands of systems fielded, the FLIR Star SAFIRE III provides extremely reliable high performance. Along with superior image stabilization and long-range imaging, Star SAFIRE III features internal navigation for precise targeting, a MWIR thermal imager, optional EO color and low-light cameras, and multiple laser payload options. The system is fully hardened for military fixed-wing and helicopter operations, and it operates continuously in all conditions – even while sitting on the tarmac with no airflow.

Multiple sensors allow the Star SAFIRE III to detect, recognize, and positively identify targets with pinpoint precision at long ranges – capabilities that have been proven time and again on the battlefield. Mission crews can remain undetected at safe standoff distances while viewing high-resolution imagery in narrow and wide fields-of-view. With flexible integration options on multiple platforms, the Star SAFIRE III is optimal for program-centric airborne intelligence, surveillance, reconnaissance, patrol, and search and rescue missions.

FEATURES

OPTIMIZED USABILITY

View and track ground locations using the fully-embedded IMU; follow moving targets with the multi-mode Autotracker.

MULTI-MISSION CAPABLE

Can be used in applications as diverse as land force protection, shipboard open ocean and littoral patrol, and long-range airborne reconnaissance.

IMAGE BLENDING

Combine critical spectral information from the IR imager with the Image Intensified Low-Light camera or long-range Spotter Scope.

PRECISION TARGETING

Tightly coupled navigation delivers accurate, robust CAT 1 target coordinate-generation for faster, more confident targeting.

RELIABLE 24/7 OPERATION

Mature product with high MTBF and proven combat survivability in demanding arctic and desert environments.

APPLICATIONS

SEARCH & RESCUE

RECONNAISSANCE

BORDER AND COASTAL PATROL

TARGET IDENTIFICATION

FORCE PROTECTION

UAV PLATFORMS

SPECIFICATIONS

THERMAL IMAGER

Sensor type	640 x 512 InSb focal plane array
Wavelength	3-5 μ m response
FOVs	25° to 0.35°
Zoom ratio	71x

COLOR ZOOM CAMERA (OPTIONAL)

Sensor type	Color CCD-TV
Resolution	525 / 625 line (NTSC/PAL)
FOVs	28° to 2.7°
Zoom ratio	18x (+12x E-Zoom)

SPOTTER SCOPE (OPTIONAL)

Sensor type	3-chip Color CCD
Resolution	800 line
FOVs	5.4° to 0.29° (Matched to IR FOVs)

LOW-LIGHT CAMERA (OPTIONAL)

Sensor type	Image intensified
FOVs	5.4° to 0.7° (Matched to IR FOVs)

LASER PAYLOADS (OPTIONAL)

Rangefinder	Max. range 25 km +/- 5 m Classification: Class 1 (eyesafe)
Illuminator	Power: 1 W or 2 W options Classification: Class 4
Pointer	Power: 100 mW Classification: Class 3b

DIGITAL IMU/GPS+ (OPTIONAL)

Tightly-coupled, fully-integrated, IMU and GPS for geo-pointing and target geo-location

SYSTEM PERFORMANCE

System type	5 axis stabilization
Az. coverage	360° continuous
El. coverage	+30° to -120°
Airspeed	405 KIAS

SYSTEM INTERFACES

Analog video	NTSC/PAL
Control	RS-232, RS-422, Ergonomic Laptop or Handheld
Data	RS-232, RS-422, ARINC 419/429, MIL-STD-1553B

ENVIRONMENTAL

Standards	MIL-STD-810E and MIL-STD-461F
Operating temperature	-40°C to 55°C

POWER REQUIREMENTS

Voltage	22-29 VDC (per MIL-STD-704E)
Consumption	200 W (650 W max)

DIMENSIONS, WEIGHT & MOUNTING

TFU Size	15.0" x 17.5" (380 mm x 450 mm)
TFU Weight	<98 lbs (<44 kg)
CEU Size	10.0" x 7.5" x 12.5" (254 mm x 191 mm x 318 mm)
CEU Weight	23.0 lbs (10.4 kg)
Mounting	Compatible with Star SAFIRE family

Other Options & Accessories

Automatic Target Tracker, Navigation/Radar Interfaces, Quick-Disconnect Mounts, Displays and Recorders, Moving Map Systems, Video Downlinks



AMERICAS

FLIR Systems, Inc.
Corporate Headquarters
27700 SW Parkway Ave
Wilsonville, OR 97070
Office: +1 877.773.3547

FLIR Systems, Inc.
DC Headquarters
1201 S. Joyce Street
Suite C006
Arlington, VA 22202
Office: +1 703.682.3400

EUROPE

FLIR Systems
2 Kings Hill Avenue - Kings Hill
West Malling, Kent ME19 4AQ
United Kingdom
Office: +44 (0)1732 220 011
Fax: +44 (0)1732 843 707

FLIR Systems AB
Antennvägen 6,
PO Box 737
SE-187 66 Täby
Sweden
Office: +46 (0)8 753 25 00

MIDDLE EAST

FLIR Systems B.V. - Abu Dhabi
Wadi Al Fey St.
Building 60, Office # 302
New Ministries Exit / Khalifa Park Area
Abu Dhabi, U.A.E.
Office: +971 2 666 1561
e-Fax: +1 503 914 1591

FLIR Systems Saudi Arabia
Office 127, First Floor
Akaria Plaza Building, Olaya Street
Riyadh, 11481, Saudi Arabia
Office: +966 11 464 5323
Fax: +966 11 464 0438

ASIA

FLIR Systems Japan K.K.
Meguro Tokyuu Bldg. 5F,
2-13-17
Kami-Osaki, Shinagawa-ku.
Tokyo, 141-0021, Japan
Office: +81-3-6721-6648

For More Information contact
surveillance_sales@flir.com

www.flir.com
NASDAQ: FLIR

Equipment described herein is subject to US export regulations and may require a license prior to export. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2019 FLIR Systems, Inc. All rights reserved. 01/10/19

18-2521-SUR-StarSafireIIISpecsheetLTR



The World's Sixth Sense®