

FLIR *ITS-Series Dual* *AID 316L*

Intelligent Dual vision camera for
Automatic Incident & Fire detection



FLIR ITS-Series Dual AID cameras combine best-in-class thermal and visual imaging technology with advanced video analytics to provide a complete solution for automatic incident detection, data collection and early fire detection. FLIR's traffic video analytics have proven their effectiveness worldwide along highways and in tunnels and are now combined with the power of thermal imaging that allows traffic operators to see clearly in total darkness, in bad weather and over a long range.

DAYLIGHT CAMERA

All versions are equipped with a daylight/low light camera with a motorized optical zoom. The video output of the thermal imaging and daylight/low light camera are simultaneously available.



AUTOMATIC INCIDENT DETECTION

The FLIR ITS-Series Dual AID camera provides critical traffic information, supporting traffic operators with alerts on stopped vehicles, wrong-way drivers, pedestrians, lost cargo, traffic flow data and much more.

THERMAL IMAGING

Thermal imaging cameras outperform other camera technologies by detecting the heat energy given off by everything in their field of view. Because they see heat, not visible light, they don't get confused by sun glare, darkness, headlights, shadows, wet streets, snow and fog, like conventional video cameras do. FLIR thermal cameras do not get damaged at all by looking continuously in direct sun light.

THERMAL EARLY FIRE DETECTION

The FLIR ITS-Series Dual AID can measure the temperature of any object in its field of view. This unique capability allows detecting fires at an early stage over the full detection range. Unlike other fire detection technologies, no contact is required with flames or heated gasses, nor is any smoke propagation needed for the camera to detect excessive heat generated by fire or another vehicle malfunction. As a result, the thermal camera is capable of detecting fires within seconds of ignition, long before any traditional fire detection system can trigger an alarm. The intelligent fire detection algorithm takes into account multiple parameters, including size, dynamics, growth rate, movement, etc..., resulting in unprecedented fire detection accuracy.



SEE THROUGH SMOKE

Thermal cameras can penetrate smoke and as such provide a better view in case of fire. This enhanced visibility can help guide emergency personnel to locate people inside the tunnel and save lives in critical situations.

DESIGNED FOR USE IN HARSH ENVIRONMENTS

Extremely rugged in 316L stainless steel housing. The vital core is well protected, meeting IP66 & IP67 requirements, against dust, water ingress and immersion.

Specifications

Thermal image	
Detector type	Focal Plane Array (FPA), uncooled Vanadium Oxide Microbolometer
Spectral range	7.5 to 13.5 μ m
Resolution	640 x 480
Focal	9/13/19/25mm
Image frequency	NTSC: 30Hz PAL: 25Hz
Image processing	Automatic Gain Control (AGC), Digital Detail Enhancement (DDE)
Visual image	
Image sensor	1/3" Sony CMOS sensor
Max. Resolution	1920 x 1080
Optical zoom	10x motorized optical zoom
Focal length	5-50mm
Image presentation	
Video over Ethernet	Two independent channels for each camera (4 total) of streaming H.264 or M-JPEG
Streaming Resolutions	Visual : up to 1920 x 1080 @ 30 Hz Thermal: up to 640 x 480 @ 30 Hz
Analytics	
Automatic Incident Detection	<p>Traffic events Stopped vehicle, Speed drop, Levels of service, Overspeed, Wrong-way drivers, Traffic congestion, underspeed</p> <p>Non-traffic events Smoke in tunnel, Pedestrian, Fallen object</p> <p>Technical alarms Image quality, Camera tampering</p>
Traffic Data Collection	<p>Traffic flow data per lane Traffic flow speed, zone occupancy</p> <p>Integrated vehicle traffic data Average speed per vehicle class per lane (headway, gap time per length, class per lane), occupancy</p> <p>Individual vehicle traffic data Speed, gap time, headway, vehicle classification</p>
Fire detection	Early fire detection in tunnels
Power	
Power options	230 Vac, 24Vac or dc, PoE camera only, PoE+ for camera & heater
Consumption	12W heater off, 24W heater on
Environmental	
Operating temp. range	-30°C to +65°C
Relative humidity	0% to 100%, no condensation
Ingress protection	IP66 / IP67
Network	
Interface	10/100 Mbps Ethernet (RJ-45), internal SFP slot optional
Supported Protocols	IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMPv1/2/3, QoS, ONVIF, 802.1X
API	ONVIF Profile S
Standard package	
Dual imaging camera, operator manual	
Mechanical	
Housing material	Stainless steel 316L
Mounting	Wall/pole/ceiling mount
Dimensions(HxWxD)	Housing only: 71 x 130 x300 mm With bracket: 201x134x408 mm
Weight	4kg
Cable glands	2xM20 or IP67 network and power connector

PORTLAND
Corporate Headquarters
FLIR Systems, Inc.
27700 SW Parkway Ave.
Wilsonville, OR 97070
USA
PH: +1 866.477.3687

SANTA BARBARA
FLIR Systems, Inc.
70 Castilian Drive.
Goleta, CA 93117
USA
PH: +1 866.477.3687

BELGIUM
FLIR Systems Trading
Belgium BVBA
Luxemburgstraat 2
2321 Meer
Belgium
PH: +32 (0) 3665 5100

FLIR ITS
Hospitaalweg 1B
B-8510 Marke
Belgium
PH: +32 (0)56 37 22 00

UK
FLIR Systems UK
2 Kings Hill Avenue
Kings Hill
West Malling - Kent
ME19 4AQ
United Kingdom
PH: +44 (0)1732 220 011

www.flir.com
NASDAQ: FLIR

Specifications are subject to change without notice
©Copyright 2017, FLIR Systems, Inc. All other brand and product names are trademarks of their respective owners. The images displayed may not be representative of the actual resolution of the camera shown. Images for illustrative purposes only. 18-1323 (Revised 06/18)