



HIGH-DEFINITION LONG-RANGE SURVEILLANCE SYSTEM

FLIR Ranger® HDC MS

FLIR Ranger® HDC MS increases mission effectiveness, extending surveillance through darkness, distance, and especially when “bad weather is good smuggling weather.” This multisensor system integrates long-range, mid-wave thermal imaging with a variety of powerful daylight sensors, and optionally a laser range finder, GPS, digital magnetic compass, and automatic video tracker. Read ship names or license plates, or watch the scene from a safe standoff distance of up to and beyond the 15 km range.

Integrated fog and heat turbulence filters penetrate particulates and eliminate image distortion caused by atmospheric conditions. Pan-tilt 1280x720 HD MWIR and visible cameras with powerful continuous-zoom telescopes help detect and identify more targets from farther away. Ranger HDC MS assesses threats while discerning between nuisance alarms and those requiring interdiction for border, coastal surveillance, and force protection surveillance. Besides increasing the mission effectiveness in bad weather, it also helps forces act faster, increase uptime, and reduce cyber risks.

FEATURES

SEE MORE IN WIDE FORMAT

HD imagery captures twice as much of a scene compared to legacy standard resolution.

EXTEND MISSION CAPABILITY IN BAD WEATHER

See through fog and haze with the integrated fog filter, and through turbulent air with Merlin ASX turbulence filter.

ACT FASTER WITH HIGHER RESOLUTION IMAGERY

Shorten the time between target detection and counter measures with more comprehensive intel from HD details and a fast, accurate pan-tilt that's perfect for slew-to-cue applications.

INCREASE UPTIME AND REDUCE COSTS

New long-life core doubles uptime and significantly reduces the downtime, maintenance, and logistic costs compared to previous generations.

REDUCE CYBER RISK

A cyber security tool provides high resistance to hacker attacks that can compromise mission effectiveness.

APPLICATIONS

BORDER SECURITY

COASTAL SURVEILLANCE

FORCE PROTECTION

INDUSTRIAL FACILITY

CRITICAL INFRASTRUCTURE SECURITY

AIR & SEA PORTS

VEHICLE & MAN-PORTABLE CAPABILITIES

SPECIFICATIONS

Thermal Imaging	Ranger HDC 800		Ranger HDC 1200	
Detector type	Indium Antimonide (InSb): 1280x720 pixels			
Spectral Range	3 – 5µm			
Field-of-view	1.35° (H) to 30° (H), (±7%), 16:9 format		0.92° (H) to 20.4° (H), (+/-%), 16:9 format	
Continuous zoom	Optical zoom 22x, Digital zoom 16x			
Color TV	HD LR-TV 750/720	HD LR-TV 750/1080	HD LR-TV 1000/720	HD LR-TV 1000/1080
Sensor format	1/2" Color CCD, 1280 x 720 pixels	1/2" Color CMOS, 1920 x 1080 pixels	1/2" Color CCD, 1280 x 720 pixels	1/2" Color CMOS, 1920 x 1080 pixels
Focal length	12.5 – 750 mm 25 – 1500 mm with 2x extender		16.7 – 1000 mm 33.4 – 2000 mm with 2x extender	
Narrow field-of-view	(H) 0.54°, 0.27° with 2x extender	(H) 0.51°, 0.25° with 2x extender	(H) 0.4°, 0.2° with 2x extender	(H) 0.38°, 0.19° with 2x extender
Wide field-of-view	(H) 31.5°	(H) 29.6°	(H) 22.8°	(H) 22.4°
Optical zoom	60x, 120x with 2x extender			
Min sensitivity	3 lux	1 lux	3 lux, 0.5 lux @10Hz	1 lux, 0.17 lux @10Hz
Fog filter	no	no	yes	yes
Pan-tilt				
Az Range; Az velocity	n x 360°; 0.03° – 100° / sec continuous			
EI Range; EI velocity	± 90°; 0.03° – 100° / sec			
Accuracy	± 0.5 mrad			
Resolution	0.2 mrad			
Options				
LRF	Optionally available			
GPS	Optionally available			
DMC	Optionally available			
Merlin ASX Turbulence filter	Optionally available, for IR camera or Color camera or for both IR camera and Color camera			
Automatic Video tracker	Standard option			
Electronic image stabilization	Standard option			
Interfaces				
Ethernet	Command and control, all functions and h. 264 video			
Video out	2x HD SDI, and h.264			
4-wire RS-485 full duplex	Command and control all functions			
Power				
Input voltage	+31 VDC (operates between 18-32VDC)			



AMERICAS

FLIR Systems, Inc.
Corporate Headquarters
27700 SW Parkway Ave
Wilsonville, OR 97070
Office: +1 877.773.3547

FLIR Systems, Inc.
DC Headquarters
1201 S. Joyce Street
Suite C006
Arlington, VA 22202
Office: +1 703.682.3400

EUROPE

FLIR Systems
2 Kings Hill Avenue - Kings Hill
West Malling, Kent ME19 4AQ
United Kingdom
Office: +44 (0)1732 220 011
Fax: +44 (0)1732 843 707

FLIR Systems AB
Antennvägen 6,
PO Box 737
SE-187 66 Täby
Sweden
Office: +46 (0)8 753 25 00

MIDDLE EAST

FLIR Systems B.V. - Abu Dhabi
Wadi Al Fey St.
Building 60, Office # 302
New Ministries Exit / Khalifa Park Area
Abu Dhabi, U.A.E.
Office: +971 2 666 1561
e-Fax: +1 503 914 1591

FLIR Systems Saudi Arabia
Office 127, First Floor
Akaria Plaza Building, Olaya Street
Riyadh, 11481, Saudi Arabia
Office: +966 11 464 5323
Fax: +966 11 464 0438

ASIA

FLIR Systems Japan K.K.
Meguro Tokyu Bldg. 5F,
2-13-17
Kami-Osaki, Shinagawa-ku.
Tokyo, 141-0021, Japan
Office: +81-3-6721-6648

For More Information contact
surveillance_sales@flir.com

www.flir.com
NASDAQ: FLIR

Equipment described herein is subject to US export regulations and may require a license prior to export. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2019 FLIR Systems, Inc. All rights reserved. Revised 01/11/19

18-2138-SUR-Ranger-HDC-MS-SSA4



The World's Sixth Sense®