




THERMAL IMAGING CAMERA WITH VIEWFINDER

FLIR T800-Series™

The FLIR T800-Series is the new standard in predictive/preventative maintenance tools for utility, electro-mechanical, manufacturing, and building diagnostics professionals. The T840 and T860 feature on-board Inspection Routing that speeds data collection and reporting by helping users plan out surveys and then organizing images and data by location. An integrated eyepiece viewfinder, bright 4-inch color LCD, and thoughtful ergonomic design allow inspectors to comfortably survey equipment for signs of failure—even in challenging lighting conditions. Advanced features such as 1-Touch Level/Span contrast enhancement and tack-sharp laser-assisted autofocus ensure the camera takes accurate temperature measurements every time. Maintain consistent uptime through regular maintenance routines with this flexible and innovative IR camera.

www.flir.com/T800-Series



IMPROVE WORKFLOW EFFICIENCIES

On-board routing and new FLIR software aid in the collection and management of critical data

- Develop and upload routes to the camera for streamlined inspections of critical assets within a plant or facility
- Acquire temperature data, thermal, and visual imagery in a logical sequence for faster preventative/predictive maintenance procedures
- Automate data management and reporting through easy transfer of organized files to FLIR Thermal Studio Pro

AVOID COSTLY OUTAGES AND COMPONENT FAILURES

Assess the thermal health of equipment and systems from any angle, in any lighting conditions

- Adapt to any work environment with a vibrant 4" color LCD display and an integrated eye-piece viewfinder
- Image targets overhead or down low without strain thanks to the 180° rotating optical block and ergonomic design
- Accurately measure small targets over long distance or in large scenes with the optional 6° telephoto lens

MAKE CRITICAL DECISIONS QUICKLY

Save time and share data faster to increase in-field efficiency

- Ensure precision measurement with laser-assisted autofocus, 1-Touch Level/ Span, and exceptional temperature accuracy
- Avoid diagnostic errors with industry-leading image clarity from FLIR Vision Processing™, combining MSX®, UltraMax®, and proprietary adaptive filtering algorithms
- Optimize workflows with reporting features such as built-in voice annotation, customizable work folders, and Wi-Fi sync to the FLIR Tools® App

SPECIFICATIONS

Imaging and optical data	T840	T860
IR resolution	464 × 348 (161,472 pixels, 645,888 with UltraMax®)	640 × 480 (307,200 pixels, 1,228,800 with UltraMax®)
Detector pitch	17 µm	12 µm
Object temperature range	-20°C to 120°C (-4°F to 248°F); 0°C to 650°C (32°F to 1202°F); 300°C to 1500°C (572°F to 2732°F)	-20°C to 120°C (-4°F to 248°F); 0°C to 650°C (32°F to 1202°F); 300°C to 2000°C (572°F to 3632°F)
Digital zoom	1-6× continuous	1-8× continuous
Macro Mode (24° lens option)	71 µm min. focus distance	50 µm min. focus distance
Detector data		
Detector type and pitch	Uncooled microbolometer	
Thermal sensitivity/NETD	<30 mK @ 30°C (42° lens)	
Spectral range	7.5–14.0 µm	
Image frequency	30 Hz	
Lens identification	Automatic	
F-number	f/1.1 (42° lens) f/1.3 (24° lens), f/1.5 (14° lens), f/1.35 (6° lens)	
Focus	Continuous with laser distance meter (LDM), One-shot LDM, One-shot contrast, manual	
Minimum focus distance	42° lens: 0.15 m 24° lens: 0.15 m; optional macro mode 14° lens: 1.0 m 6° lens: 5.0 m	
Programmable buttons	2	
Image presentation		
Display	4-inch, 640 × 480 pixel touchscreen LCD with auto-rotation	
Digital camera	5 MP with built-in LED photo/video lamp	
Color palettes	Iron, Gray, Rainbow, Arctic, Lava, Rainbow HC	
Image modes	Infrared, visual, MSX®, Picture-in-picture	
Picture-in-picture	Resizable and movable	
UltraMax®	Activated in menu and processed in FLIR Tools®	
Measurement and analysis		
Accuracy	±2°C (±3.6°F) or ±2% of reading	
Spotmeter and area	3 each in live mode	
Measurement presets	No measurement, Center spot, Hot spot, Cold spot, User Preset 1, User Preset 2	

Specifications are subject to change without notice.
For the most up-to-date specs, go to www.flir.com

Measurement and analysis - Cont.	
Laser pointer	Yes
Laser distance meter	Yes; dedicated button, displays distance on-screen
On-screen area measurement	Yes; calculates area inside measurement box in m ² or ft ²
Annotations	
Inspection Routing	File created in FLIR Thermal Studio Pro using FLIR Route Creator plug-in
Voice	60 sec. recording added to still images or video via built-in mic (has speaker) or via Bluetooth*
Text	Predefined list or touchscreen keyboard
Image Sketch	Infrared images, from touchscreen
GPS	Automatic image tagging
METERLiNK®	Yes; connects to METERLiNK-enabled FLIR meters
Image storage	
Storage media	Removable SD card
Image file format	Standard JPEG with measurement data included
Time lapse (Infrared)	10 sec to 24 hrs
Video recording and streaming	
Radiometric IR video recording	Real-time radiometric recording (.csq)
Non-radiometric IR or visual video	H.264 to memory card
Radiometric IR video streaming	Compressed, over UVC
Non-radiometric IR video streaming	H.264, MPEG-4 over Wi-Fi; MJPEG over UVC or Wi-Fi
Communication interfaces	USB 2.0, Bluetooth, Wi-Fi, DisplayPort
Video out	DisplayPort
Additional data	
Languages	21
Battery type	Li-ion battery, charged in camera or on separate charger
Battery operation	Approximately 4 hours at 25°C (77°F)
Operating temperature range	-15°C to 50°C (5°F to 122°F)
Shock/Vibration/Encapsulation	25 g (IEC 60068-2-27) / 2 g (IEC 60068-2-6) / IP54
Safety	EN/UL/CSA/PSE 60950-1
Weight (including battery)	1.4 kg (3.1 lbs)
Size (l × w × h, lens vertical)	150.5 × 201.3 × 84.1 mm (5.9 × 7.9 × 3.3 in)
Package contents	
Infrared camera, lens, front and rear lens caps, cleaning cloth, small eyecup, rechargeable battery (2 ea.), charger power supply, 15 W/3 A power supply, straps (lens cap, neck), cables (USB 2.0 A to USB Type-C, USB Type-C to USB Type-C, USB Type-C to HDMI and PD adapter), 8 GB SD card, printed documentation	

CORPORATE HEADQUARTERS
FLIR Systems, Inc.
27700 SW Parkway Ave.
Wilsonville, OR 97070
USA
PH: +1 866.477.3687

LATIN AMERICA
FLIR Systems Brasil
Av. Antonio Bardella, 320
Sorocaba, SP 18085-852
Brasil
PH: +55 15 3238 8070

EUROPE
FLIR Commercial Systems
Luxemburgstraat 2
2321 Meer
Belgium
PH: +32 (0) 3665 5100

ASIA
FLIR Systems Co. Ltd.
Room 1613 – 16, Tower 2
Grand Central Plaza,
No. 138 Shatin Rural Committee Road
Shatin, New Territories
Hong Kong
PH: +852 2792 8955

www.flir.com
NASDAQ: FLIR

Equipment described herein is subject to US export regulations and may require a license prior to export. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2019 FLIR Systems, Inc. All rights reserved. 09/3/19

18-2903-INS-PPM - A4



The World's Sixth Sense®