

THERMOSIGHT™ V4000E

Long Range Thermal Sight for Remote
Weapon Systems

APPLICATIONS

RECONNAISSANCE

FORCE PROTECTION

TARGET ACQUISITION



The V4000E is a cooled midwave infrared (MWIR) sight for long-range remote weapon systems designed to maximize performance and stand off range at an affordable price point. The V4000E has a wide field of view of 10 degrees to scan the scene for threats and targets and a narrow 2 degrees field of view for target assessment and accurate aiming. Loaded with FLIR advanced image processing algorithms, V4000E helps provide reliable image clarity through the entire shooting sequence under various conditions, and minimizes time to accurate shot. Mission ready and field proven by the US Army.

The V4000E has superior automatic detail enhancement (ADE), better handling of noise amplification, improved renderings for hot objects, minimized halo effects and more to help the operator achieve faster and more accurate target detection and identification without manual adjustment.

FEATURES

GREAT STANDOFF RANGE

Provides the ability to identify a tank target at nearly 4km thanks to its powerful optics and a cooled MWIR detector.

ACCURATE AIMING SOLUTION

Perfect solution for accurate aiming with longer range, larger caliber weapon systems such as 30mm as well as for missiles such as the Javelin.

FIELD PROVEN

In use with the US Army, and tested and qualified to MIL-STBD 810.

EFFICIENT

Requires little or no manual tuning thanks to FLIR advanced image processing algorithms.

POWERFUL PERFORMANCE

Powerful long range performance in a relatively small package.

SPECIFICATIONS

SYSTEM CHARACTERISTICS	
THERMAL IMAGER	FLIR THERMOSIGHT V4000E
Sensor Technology	Indium Antimonide (InSb)
Array Format	640 x 480 pixels
Spectral Band	3-5 μm
Narrow Field of View	2°x1.5°
Wide Field of view	10°x7.5°
Focus	One shot Auto Focus and Manual Focus
VIDEO OUT	
Video format	PAL or NTSC
Video latency	≤40ms
INTERFACING	
Input Voltage	19-29 VDC
Consumption	Average <31 W, peak <42 W
SIZE AND WEIGHT	
Depth	290 mm (approx.)
Width	172 mm (approx.)
Height	180 mm (approx.)
Weight	Approx 5kg / 11lbs
ENVIRONMENTAL	
Operating Temperature Range	-40°C to +55°C, MIL-STD 810
Non-Operating Temperature Range	-46°C to +71°C, MIL-STD 810
Ballistic shock	IAW MIL-STD-810, Method 522.1



AMERICAS

27700 SW Parkway Ave
Wilsonville, OR 97070

EUROPE

2 Kings Hill Avenue - Kings Hill
West Malling, Kent ME19 4AQ
United Kingdom

Antennv gen 6,
PO Box 737
SE-187 66 Täby
Sweden

MIDDLE EAST

Wadi Al Fey St.
Building 60, Office # 302
New Ministries Exit /
Khalifa Park Area
Abu Dhabi, U.A.E.

Office 127, First Floor
Akaria Plaza Building, Olaya Street
Riyadh, 11481, Saudi Arabia

ASIA

Meguro Tokyu Bldg. 5F,
2-13-17
Kami-Osaki, Shinagawa-ku.
Tokyo, 141-0021, Japan

This product is subject to United States export regulations and may require US authorization prior to export, reexport, or transfer to non-US persons or parties. Diversion contrary to US law is prohibited. For assistance with confirming the Jurisdiction & Classification of Teledyne FLIR, LLC products, please contact exportquestions@flir.com. ©2021 Teledyne FLIR LLC. All rights reserved.

Revised on 08/31/21
Thermosight V4000E_Datasheet-A4 21-0811